

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Protective Lacquer JE730

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Company name:	Jentner Plating Technology GmbH	
Street:	Johann-Staib-Strasse 2	
Place:	D-75179 Pforzheim	
Telephone:	+49 (0)7231 418094 0	Telefax: +49 (0)7231 418094 77
e-mail:	info@jentner.de	
Contact person:	Department of Chemistry	
Internet:	www.jentner.de	
Responsible Department:	Poison Information Center of the University of Freiburg.	

1.4. Emergency telephone number:

0049 (0)761 19240 - 24 h german and english

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

May cause drowsiness or dizziness.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

butan-1-ol; n-butanol

propan-2-ol; isopropyl alcohol; isopropanol

ethyl acetate

2-methylpropan-1-ol; iso-butanol

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 2 of 11

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of Water and soap..
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P233 Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container to an officially registered waste disposal company.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 3 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
71-36-3	butan-1-ol; n-butanol			2,5-10 %
	200-751-6	603-004-00-6		
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			2,5-10 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
141-78-6	ethyl acetate			2,5-10 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
78-83-1	2-methylpropan-1-ol; iso-butanol			2,5-10 %
	201-148-0	603-108-00-1		
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H315 H318 H335 H336			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO₂) Foam Extinguishing powder.**Unsuitable extinguishing media**

Water.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 4 of 11

with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Coatings and paints, thinners, paint removers

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 5 of 11

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-83-1	2-Methylpropan-1-ol	50	154		TWA (8 h)	WEL
		75	231		STEL (15 min)	WEL
71-36-3	Butan-1-ol	50	154		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
 Colour: colourless
 Odour: characteristic
 pH-Value: n.a.

Changes in the physical state

Melting point: not determined
 Initial boiling point and boiling range: 78 °C

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 6 of 11

Flash point: 13 °C

Sustaining combustion: Sustaining combustion

Flammability

Solid: not applicable

Gas: not applicable

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits: 0,7 vol. %

Upper explosion limits: 15 vol. %

Auto-ignition temperature

Solid: not applicable

Gas: 245 °C

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Vapour pressure:
(at 50 °C) 1099,9999999 hPaDensity: 0,88 g/cm³Water solubility: The study does not need to be conducted
because the substance is known to be
insoluble in water.**Solubility in other solvents**

not determined

Partition coefficient: not determined

Viscosity / kinematic:
(at 20 °C) 70 mm²/s

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 7 of 11

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
71-36-3	butan-1-ol; n-butanol				
	oral	ATE 500 mg/kg			
78-83-1	2-methylpropan-1-ol; iso-butanol				
	oral	LD50 > 2830 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 24 mg/l	Rat		

Irritation and corrosivity

Causes serious eye damage.

Causes skin irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
78-83-1	2-methylpropan-1-ol; iso-butanol					
	Acute fish toxicity	LC50 1430 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 1250 mg/l		Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 1439 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 8 of 11

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
78-83-1	2-methylpropan-1-ol; iso-butanol	0,79

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:** UN 1263**14.2. UN proper shipping name:** Paint**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Classification code: F1
 Special Provisions: 163 367 640D 650
 Limited quantity: 5 L
 Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 9 of 11

14.1. UN number: UN 1263**14.2. UN proper shipping name:** Paint**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Classification code: F1

Special Provisions: 163 367 640D 650

Limited quantity: 5 L

Excepted quantity: E2

Marine transport (IMDG)**14.1. UN number:** UN 1263**14.2. UN proper shipping name:** Paint**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Special Provisions: 163, 367

Limited quantity: 5 L

Excepted quantity: E2

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:** UN 1263**14.2. UN proper shipping name:** Paint**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Special Provisions: A3 A72 A192

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 10 of 11

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 7 % (61,6 g/l)
2004/42/EC (VOC): 7 % (61,6 g/l)
Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water contaminating class (D): 3 - highly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements

Jentner Plating Technology GmbH
Safety Data Sheet

according to Regulation (EC) No 1907/2006



JENTNER
PLATING TECHNOLOGY

Protective Lacquer JE730

Revision date: 23.07.2019

Product code: 10293.0000

Page 11 of 11

of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)