

Covering Varnish JE703

Description

The Covering Varnish JE703 is suitable for covering surfaces that should be plated only partially. Especially with larger areas the use is recommended. The masking lacquer is very easy to apply and very resistant to the galvanic electrolytes. This paint does not hardens completely and is perfect for short to long electroplating times

Operating conditions

The product has to be grease-free and clean. We recommend before painting ultrasonic or electrolytic degreasing and then to dry.

The masking lacquer can be according to the dilution applied with a brush, a roller or with a spraying gun. The processing mode can be tested by preliminary tests.

Too long degreasing times like ultrasonic or electrolytic degreasing should be avoided after the application.

Drying

Dry for plating	20-80 min
Ready for assembly	approx. 4 h
Completely dried out	approx. 14 h

Removing

To remove the masking lacquer the solvent for masking lacquer JE725 or acetone can be used.

Note

If problems arise, 5% formic acid can be added to the JE725.

Storage

Store it in closed containers and separated from food products in suitable special marked boxes.

Risks/Disposal

The paint is flammable and irritating to the eyes and the skin. Hand and eye protection is recommended.

The hardened paint can be disposed of as plastic waste. Dispose of the liquid waste in according with applicable legislation, ask your local waste disposal company.

**Please note our
Safety Data Sheet!**